



Technical features

- Use with reverse acting rupture discs
- Insert holder design
 - Can be pre-assembled in the workshop
 - Ensure that the bursting disc is not damaged when disassembling
- The rupture disc arch is contained in the holder assembly
 - Prevent damage to rupture discs when mounting to flanges
- Size from 1" to 12"
- Standard materials: stainless steel, carbon steel
- Easy to disassemble without special tools
- Suitable for 1"-12" standard flanges
- With stainless steel nameplate containing parameters and a flow arrow

Options

tee, nozzle, pressure gauge, excess flow valve, lifting bolts, special coating

Size & Specification of Holders

Size		Flange Class		Height		O.D	Est. Weight
in	mm	ANSI	DIN	LJ mm	YJ mm	mm	Kg
1	25	150	10/16	46	46	62	0.8
		300/600	25/40			66	0.9
1/2	40	150	10/16	46	51	82	1.3
		300/600	25/40			88	1.6
2	50	150	10/16	46	51	96	1.8
		300/600	25/40			100	2.0
3	80	150	10/16	46	51	128	2.6
		300/600	25/40			132	2.9
4	100	150	10/16	46	56	152	3.0
		300/600	25/40			156	3.4
6	150	150	10/16	56	61	206	5.9
		300/600	25/40			216	7.5
8	200	150	10/16	61	66	256	8.3
		300/600	25/40			274	12.2
10	250	150	10/16	71	76	310	13.0
		300/600	25/40			330	19.0
12	300	150	10/16	76	81	372	18.2
		300/600	25/40			389	24.7
14	350	150	10/16	91	91	418	26.8
		300/600	25/40			448	41.5
16	400	150	10/16	106	106	489	45.3
		300/600	25/40			503	54.4
18	450	150	10/16	116	116	528	53.2
		300/600	25/40			548	68.7
20	500	150	10/16	121	121	584	60.2
		300/600	25/40			609	82.7
24	600	150	10/16	126	126	690	78.7
		300/600	25/40			720	112.0